

CAPE GEORGE COLONY CLUB
 61 CAPE GEORGE DRIVE
 PORT TOWNSEND, WA 98368

PHONE: (360) 385-1177
 FAX: (360) 385-3038

DRIVEWAY CONNECTION PERMIT APPLICATION

Name:		Date:
Mailing Street Address:	City:	State & Zip
Telephone (day):		Telephone (evening):
Legal Location: Lot No. _____ Colony <input type="checkbox"/> Div No.: _____ Village <input type="checkbox"/> Blk No.: _____ Highlands <input type="checkbox"/>	Street Name and No.:	

Number of Driveway Connections:	Select One: <input type="checkbox"/> Asphalt <input type="checkbox"/> Concrete <input type="checkbox"/> Other
---------------------------------	---

Driveway connection must be installed in accordance with Typical Driveway Connection (BG06-a) and unless other conditions apply, be completed within one year of issuance of permit or within 90 days of occupancy whichever occurs sooner.

Contact Road Committee Chair upon completion of your project	
Owner's Signature:	Date:

----- CLUB USE ONLY -----

We have reviewed this application and recommend: _____Approval _____Disapproval	
Reason for disapproval:	
Other Conditions:	
Road Committee(signature): _____	Date: _____
We have inspected this project and certify it in compliance with Club Regulations.	
Road Committee(signature)_____	Date:_____

CAPE GEORGE COLONY CLUB

61 CAPE GEORGE DRIVE
PORT TOWNSEND, WA 98368

PHONE: (360) 385-1177
FAX: (360) 385-3038

TYPICAL DRIVEWAY CONNECTION

1. A six foot minimum apron from the road edge is required for all driveways.
2. Diagram of typical driveway over culvert is pictured below – disregard culvert specification for non-ditch driveways.
3. Driveway Ditch Culvert Specification:
 - a. Minimum cover – 12", with the top layers consisting of 2" of crushed rock surfacing and 2" of asphalt wearing course or 4" concrete reinforced wearing course.
 - b. Minimum culvert diameter – 12"
 - c. Culvert to match ditch center line and grade to match the original ditch bottom.
 - d. Materials – CMP-16 gauge corrugated steel storm sewer pipe with treatment #1 protective coating or ABS corrugated culvert pipe.
4. Non-Driveway Ditch Culvert Specifications:
 - a. Minimum cover – 12"
 - b. Minimum culvert diameter – 12"
 - c. Filter rock to 6" above pipe
 - d. Filter fabric over filter rock
 - e. Gravel base and/or CSTV top 6 inches
 - f. A 2' by 2' catch basin with grate must be installed for each 70' of culvert or as required by Road Committee.
 - g. Materials – perforated ABS culvert pipe (for roadway ditch only, not under driveway)

