

# CAPE GEORGE COLONY CLUB

61 CAPE GEORGE DRIVE  
PORT TOWNSEND, WA 98368

PHONE: (360) 385-1177  
FAX: (360) 385-3038

## TYPICAL DRIVEWAY CONNECTION

1. A six foot minimum apron from the road edge is required for all driveways.
2. Diagram of typical driveway over culvert is pictured below – disregard culvert specification for non-ditch driveways.
3. Driveway Ditch Culvert Specification:
  - a. Minimum cover – 12", with the top layers consisting of 2" of crushed rock surfacing and 2" of asphalt wearing course or 4" concrete reinforced wearing course.
  - b. Minimum culvert diameter – 12"
  - c. Culvert to match ditch center line and grade to match the original ditch bottom.
  - d. Materials – CMP-16 gauge corrugated steel storm sewer pipe with treatment #1 protective coating or ABS corrugated culvert pipe.
4. Non-Driveway Ditch Culvert Specifications:
  - a. Minimum cover – 12"
  - b. Minimum culvert diameter – 12"
  - c. Filter rock to 6" above pipe
  - d. Filter fabric over filter rock
  - e. Gravel base and/or CSTV top 6 inches
  - f. A 2' by 2' catch basin with grate must be installed for each 70' of culvert or as required by Road Committee.
  - g. Materials – perforated ABS culvert pipe (for roadway ditch only, not under driveway)

